

EK956009022US

PATENT

I hereby certify that this paper or fee is being deposited with the U. S. Postal Service "Express Mail Post Office - to Addressee" service under 37 CFR 1.10 on the date indicated below and is addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

1-18-02 Date of Deposit
Signature of Person Making Paper or Fee
Name of Person Signing
Date of Signature

HIGH STRENGTH AIR BAG QUALITY STEEL

Field of the Invention

This application is a continuation-in-part of pending application Serial No. 09/310,810, filed May 12, 1999, assigned to the assignee of the present invention.

The present invention relates to a process for manufacturing a steel housing, and particularly relates to a process for manufacturing a steel housing of an inflator for inflating an inflatable vehicle occupant protection device.

Background of the Invention

An inflator for inflating an inflatable vehicle occupant protection device includes a quantity of a stored gas and a body of combustible material stored in an inflator housing. An igniter is actuatable to ignite the body of combustible material. As the body

of combustible material burns, the combustion products heat the stored gas. The heated stored gas and the combustion products form an inflation fluid for inflating the vehicle occupant protection device.

5 Another inflator includes a stored inert gas and a stored combustible gas, such as hydrogen. An igniter ignites the combustible gas which heats the stored inert gas.

Summary of the Invention

10 The present invention is a process for manufacturing a steel sheet, which may be used in an inflator housing. In the process, a slug of steel is provided which is selected from the group consisting of austenitic 301 steel and austenitic 301N steel. The
15 thickness of the slug is reduced by passing the slug through a hot rolling mill while the slug is at a temperature between about 1000°C and about 1200°C, until the slug is formed into a steel sheet. The steel sheet is quenched to lower the temperature of the steel sheet
20 after the steel sheet is hot rolled. The thickness of the steel sheet is further reduced by passing the steel sheet in multiple passes through a cold rolling mill. The steel sheet is reduced in thickness between about

3% and about 13% in the last of its passes through the cold rolling mill.

Preferably, the austenitic 301 steel consists essentially of by weight less than about 0.03% carbon, less than about 2.00% manganese, less than about 0.005% sulfur, less than about 0.030% phosphorous, less than about 1.00% silicon, between about 16.00% and about 18.00% chromium, between about 6.00% and about 8.00% nickel, less than about 0.025% residual elements, and balance iron, and the austenitic 301N steel consists essentially of by weight less than about 0.03% carbon, less than about 2.00% manganese, less than about 0.005% sulfur, less than about 0.030% phosphorous, less than about 1.00% silicon, less than about 0.30% nitrogen, between about 16.00% and about 18.00% chromium, between about 6.00% and about 8.00% nickel, less than about 0.025% residual elements, and balance iron.

Brief Description of the Drawings

The foregoing and other features of the present invention will become more apparent to one skilled in the art upon consideration of the following description of the invention and the accompanying drawings in which:

Fig. 1 is a schematic view of a vehicle occupant protection apparatus embodying the present invention;

Fig. 2 is a sectional view of part of the apparatus of Fig. 1; and

Fig. 3 is a schematic block diagram illustrating a preferred embodiment of the present invention.

Description of Preferred Embodiment

Referring to Fig. 1, a vehicle occupant protection apparatus 10 includes an inflatable vehicle occupant protection device 12. In the preferred embodiment of the present invention, the inflatable vehicle occupant protection device 12 is an air bag. The inflatable vehicle occupant protection device 12 could be, for example, an inflatable seat belt, an inflatable knee bolster, an inflatable head liner an inflatable side curtain, or a knee bolster operated by an air bag.

An inflator 14 is associated with the vehicle occupant protection device 12. The inflator 14 is actuatable to direct inflation fluid to the inflatable vehicle occupant protection device 12 to inflate the inflatable vehicle occupant protection device 12.

The system also includes a crash sensor 16. The crash sensor 16 is a known device that senses a vehicle condition, such as vehicle deceleration, indicative of

a collision. The crash sensor 16 measures the magnitude and the duration of the deceleration. If the magnitude and duration of the deceleration meet predetermined threshold levels, the crash sensor either
5 transmits a signal or causes a signal to be transmitted to actuate the inflator 14. The inflatable vehicle occupant protection device 12 is then inflated and extends into the occupant compartment of the vehicle to help protect a vehicle occupant from a forceful impact
10 with parts of the vehicle.

While the inflator 14 could be a pyrotechnic inflator (not shown), in the preferred embodiment of the invention, the inflator 14 is a stored gas inflator in accordance with the invention set forth in U.S.
15 Patent No. 5,348,344, to Blumenthal et al., entitled APPARATUS FOR INFLATING A VEHICLE OCCUPANT RESTRAINT USING A MIXTURE OF GASES, and assigned to TRW Vehicle Safety Systems Inc.

As shown in Fig. 2, the inflator 14 includes a
20 housing 18. The housing 18 includes a container 20. The container 20 includes a generally cylindrical side wall 24 extending along a central axis 26 between an open end 30 and a closed end 28. The side wall 24

includes a cylindrical inner surface 32 and a cylindrical outer surface 34.

The housing 18 further includes an actuatable pyrotechnic igniter 36 secured to the closed end 28 of the housing 18 by any suitable means. The igniter 36 includes an ignitable material (not shown).

The housing 18 also includes an end cap 38 secured to the open end 30 of the container 20 by any suitable means such as a weld. The end cap 38 includes a radially extending first surface 40 and an axially centered cylindrical surface 42. The cylindrical surface 42 of the end wall 38 has a diameter smaller than the diameter of the inner surface 32 of the side wall 24 and extends axially between and connects the first surface 40 of the end cap 38 and a radially extending second surface 44 of the end cap 38. The cylindrical surface 42 defines a passage 31 through the end cap 38.

A burst disk 46 is secured to the first surface 40 of the end cap 38 by any suitable means, such as a weld. The burst disk 46 closes the passage 31. Together the burst disk 46 and the end cap 38 close the open end 30 of the side wall 24 to define a closed chamber 48 in the container 20. The chamber 48 is

defined by the end cap 38, the burst disk 46, and the cylindrical side wall 24.

A supply of gas 50 for inflating the inflatable vehicle occupant protection device 12 is stored in the chamber 48. The stored gas 50 comprises at least one inert gas. The inert gas is preferably nitrogen, argon, or a mixture of nitrogen and argon.

The stored gas 50 may also include an oxidizer gas and a fuel gas. A preferred oxidizer gas is oxygen. Preferred fuel gases include hydrogen, nitrous oxide, and/or methane. The stored gas 50 may comprise air and hydrogen.

Preferably, the stored gas 50 includes at least a small amount of a tracer gas, such as helium, for helping to detect gas leaks.

The stored gas 50 within the container 48 is under pressure. The pressure depends upon such factors as the volume of the inflatable vehicle occupant protection device 12 to be inflated, the time available for inflation, the inflation pressure desired, and the volume of the chamber 48 storing the gas. The stored gas 50 in the chamber 48 is typically at a pressure of about 2,000 to about 8,000 pounds per square inch

(psi). Preferably, the stored gas 50 in the chamber 48 is at a pressure of about 3,500 psi to about 6,500 psi.

A diffuser 52 is connected to the second surface 44 of the end cap 38 by any suitable means, such as a weld. The diffuser 52 includes a cylindrical side wall 54 coaxial with the side wall 24 of the container 20 and centered on the axis 26. The side wall 54 includes a cylindrical inner surface 56 and cylindrical outer surface 58. The diffuser has a central chamber 60. The chamber 60 is in fluid communication with the passage 31 in the end cap 38.

Fig. 3 is a schematic illustration of a method of producing the housing 18 of the inflator 14. In the method, first and second slugs of steel are provided. The steel used to form the first and second slugs of steel can be either an austenitic 301 steel or an austenitic 301N steel. The composition of the austenitic 301 steel and the austenitic 301N steel are preferably controlled. By "controlled" it is meant that the ranges for the chemical composition of the austenitic 301 steel and the austenitic 301N steel are more restricted than the ranges for the chemical composition of typical austenitic 301 steel and austenitic 301N steel.

Preferably, the austenitic 301 steel employed in the present invention consists essentially of by weight less than about 0.03% carbon, less than about 2.00% manganese, less than about 0.005% sulfur, less than about 0.030% phosphorous, less than about 1.00% silicon, between about 16.00% and about 18.00% chromium, between about 6.00% and about 8.00% nickel, and less than about 0.025% residual elements. The balance of the composition is iron. By residual elements, it is meant additional elements including titanium, lead, niobium, cobalt, aluminum, calcium, and/or tin.

Preferably, the austenitic 301N steel employed in the present invention consists essentially of by weight less than about 0.03% carbon, less than about 2.00% manganese, less than about 0.005% sulfur, less than about 0.030% phosphorous, less than about 1.00% silicon, less than about 0.30% nitrogen, between about 16.00% and about 18.00% chromium, between about 6.00% and about 8.00% nickel, and less than about 0.025% residual elements. The balance of the composition is iron. By residual elements, it is meant additional elements including titanium, lead, niobium, cobalt, aluminum, calcium, and/or tin.

The first and second slugs of steel each have a thickness. The thickness of the first and second slug can be the same or different. Preferably, the first and second slugs of steel each have a thickness of about 6.0 inches to about 7.5 inches. More preferably, the first and second slugs of steel each have a thickness of about 7.0 inches.

The first and second slugs of steel are mechanically treated to form first and second steel sheets. The first and second slugs of steel are mechanically treated by hot rolling the first and second slugs of steel. Hot rolling involves passing a product of steel, such as a slug, that has been heated through a rolling mill to substantially reduce the thickness and increase the length and width of the product. A rolling mill typically has two rolls revolving at the same peripheral speed and in opposite directions about their respective axes, i.e. clockwise and counterclockwise. The rolls are spaced so that the distance between the rolls is somewhat less than the thickness of the product of steel passing between the rolls. Under these conditions, the rolls grip the product of steel and deliver it reduced in thickness and increased in width and length.

In the present invention, the first and second slugs of steel are heated to a temperature of about 1000°C to about 1200°C and, while at a temperature of about 1000°C to about 1200°C, the first and second slugs
5 of steel are passed through the rolling mill.

Preferably, the first and second slugs of steel are heated to a temperature of about 1100°C and, while at a temperature of about 1100°C, the first and second slugs
of steel are passed through the rolling mill.

10 The first and second slugs of steel are passed through the rolling mill at least once to reduce the thickness of the first and second slugs of steel. The first and second slugs of steel may be reduced in thickness by multiple passes through the rolling mill,
15 with each pass slightly reducing the thickness of the first and second slugs of steel.

Two steel sheets are formed as a result of hot rolling the first and second slugs of steel. The steel sheets have thicknesses, which are substantially less
20 than the thickness of the first and second slugs of steel. The thickness of each of the steel sheets is uniform across the area of each of the steel sheets. One of the steel sheets preferably has a thickness of about 0.155 inches to about 0.165 inches. More

preferably, one of the steel sheets has a thickness of about 0.160 inches. The other steel sheet preferably has a thickness of about 0.090 inches to about 0.110 inches. More preferably, the other steel sheet has a thickness of about 0.100 inches.

After hot rolling, the one steel sheet and the other steel sheet are quenched by a high pressure water spray to reduce the temperature of the one steel sheet and the other steel sheet to room temperature, i.e. about 22°C.

Once the one steel sheet and the other steel sheet are at room temperature, the one steel sheet and the other steel sheet may be pickled in an acidic solution to remove any scale or oxides formed on the surface of the one steel sheet and the other steel sheet during hot rolling. Suitable pickling solutions may include sulfuric acid, phosphoric acid, nitric acid, hydrochloric acid and combinations thereof.

The one steel sheet is then further reduced in thickness by cold rolling the one steel sheet to a first uniform thickness across the area of the one steel sheet. The other steel sheet is reduced in thickness by cold rolling the other steel sheet to a

second uniform thickness across the area of the other steel sheet.

Cold rolling is similar to hot rolling except that the product of steel being rolled is unheated when it passes through the rolling mill. The cold rolling process substantially reduces the thickness of the product being cold rolled and removes small surface imperfections in the surface of the product, which are formed by hot rolling the product. By "substantially reduces the thickness" it is meant the thickness of the product of steel is reduced by greater than 2 percent. This reduction in thickness is distinguished from the reduction thickness typically encountered by temper rolling. Temper rolling, which is similar to cold rolling, usually results in a reduction of thickness of 1 to 2 percent.

The steel sheets of the present invention may be lubricated with an oil based or water based emulsion prior to cold rolling in order to reduce the heat generated by friction as the steel sheet passes between the rolls.

In the present invention, the one steel sheet and the other steel sheet are reduced in thickness by multiple passes through the cold rolling mill. Each

pass slightly reduces the thickness of each steel sheet until the one sheet reaches the first uniform thickness and the other sheet reaches the second uniform thickness. The first thickness is preferably about
5 0.072 inches to about 0.090 inches. More preferably, the first thickness is about 0.079 inches to about 0.080 inches. The second thickness is preferably about 0.043 inches to about 0.053 inches. More preferably, the second thickness is about 0.048 inches.

10 The one steel sheet is reduced in thickness about 3% to about 13% during the last pass of the one steel sheet through the cold rolling mill. Preferably, the one steel sheet is reduced in thickness between about 5% and about 13% during the last of the passes through
15 the cold rolling mill, and more preferably about 12% to about 13% during the last of the passes through the cold rolling mill. The other steel sheet is reduced in thickness less than about 50% during the last pass of the other steel sheet through the cold rolling mill.

20 The other steel sheet with the second thickness is then annealed. Annealing improves the mechanical properties of the other steel sheet. Preferably the other steel sheet is annealed at a temperature of about 1050°C for one and a half minutes in a furnace with air

atmosphere. After being annealed, the other steel sheet with the second thickness is cooled to room temperature (i.e. about 22°C) and deep drawn into the shape of the container 20 using a mechanical press.

5 The one steel sheet, after cold rolling, is formed into the endcap 38, without being annealed. The one steel sheet is not annealed after cold rolling because the mechanical properties of the one steel sheet are effective for use as an endcap. For example, the one
10 steel sheet formed from austenitic 301 steel formulated in accordance with the present invention has a tensile strength of at least about 90,000 psi, a yield strength of at least about 30,000 psi, and an elongation at break of at least about 30%. Moreover, the one steel
15 sheet formed from austenitic 301N steel formulated in accordance with the present invention has a tensile strength of at least about 95,000 psi, a yield strength of at least about 45,000 psi, and an elongation at break of at least about 40%.

20 The container 20 and endcap 38 are welded together to form the housing 18 by any suitable means, such as autogenous gas tungsten arc welding, friction, electron beam welding, or laser welding. Preferably, the

container and the endcap are welded together by laser welding.

The housing 18 so formed exhibits outstanding mechanical properties including no stress corrosion cracking in the welded portion of the housing 18, which includes the weld and the base material of the endcap 38 and the container 20 adjacent to the weld. Further, the housing 18 showed no evidence of hydrogen embrittlement in the welded portion.

Example 1

A housing for a vehicle occupant protection device was assembled from an endcap and a container formed in accordance with the present invention.

The endcap was formed by providing a first slug of austenitic 301 steel. The first slug of steel had a thickness of about 7.0 inches. The first slug of austenitic 301 steel consisted essentially of by weight less than about 0.03% carbon, less than about 2.00% manganese, less than about 0.005% sulfur, less than about 0.030% phosphorous, less than about 1.00% silicon, between about 16.00% and about 18.00% chromium, between about 6.00% and about 8.00% nickel, and less than about 0.025% residual elements. The balance of the composition is iron. By residual

elements, it is meant additional elements including titanium, lead, niobium, cobalt, aluminum, calcium, and/or tin.

5 The first slug of steel was heated to a temperature of about 1100°C, and while at a temperature of about 1100°C passed through a rolling mill to produce a first steel sheet with a uniform thickness across the area of the first steel sheet of about 0.160 inches. The first steel sheet was cooled to room temperature (i.e., about 22°C), by quenching with a high pressure water spray. Following quenching the first steel sheet was pickled to remove any scale. The first steel sheet was then reduced to a uniform thickness of about 0.079 inches by multiple passes of the first steel sheet through a cold rolling mill. The last of the passes through the cold rolling mill reduced the steel sheet's thickness by 12.36% (i.e., from a thickness of about 0.089 inches to a thickness of about 0.079 inches).

10

15

20 Samples of the first steel sheet were tested in accordance with ASTM E8/E8M and DIN/EN 10002. The first steel sheet had a had mean yield strength of at least about 101,000 psi, a mean tensile strength of about 140,000 psi, and a mean elongation of about 32%

The steel sheet was then stamped to form the endcap.

The container was formed by providing a second slug of austenitic 301 steel. The second slug of steel had a thickness of about 7.0 inches. The composition of the second slug of austenitic 301 steel was essentially the same as the composition of the first slug used to form the end cap. The second slug of steel was heated to a temperature of about 1100°C, and while at a temperature of about 1100°C passed through a rolling mill to produce a second steel sheet with a uniform thickness across the area of the steel sheet of about 0.100 inches. The second steel sheet was cooled to room temperature (i.e., about 22°C) by quenching with a high pressure water spray and then pickled to remove any scale. The second steel sheet was then reduced to a uniform thickness of about 0.048 inches by multiple pass of the second steel sheet through the cold rolling mill. The last of the passes through the cold rolling mill reduced the second steel sheet's thickness by less than 50%. The second steel sheet was annealed at a temperature of about 1050°C for about one minute and a half in an air atmosphere. After being annealed the

second steel sheet was deep drawn into the shape of the container using a mechanical press.

The endcap and the container were then welded together by laser welding to form a housing.

5 A c-ring type specimen was removed from a welded portion of the housing 18 and placed in a 3% NaCl saturated air atmosphere. The c-ring type specimen was maintained at a temperature of about 25°C and subjected to a voltage of about 1.5V from a Ag/AgCl hydrogen
10 cathode charging mechanism. Stress equivalent to 100% of the actual yield strength was applied to the c-ring type specimen for one month.

Analysis by thermal absorption spectrometry and scanning electron microscopy revealed no evidence of
15 hydrogen embrittlement in the welded portion or base metal surrounding the welded portion of the c-ring type specimen after the one month period.

Moreover, a c-ring type specimen was removed from a welded portion of the housing and placed in a 3% NaCl
20 saturated air atmosphere at a temperature of about 80°C. Stress equivalent to about 100% of the actual yield strength was applied to the c-ring type specimen for one month.

Analysis by thermal absorption spectrometry and scanning electron microscopy revealed no evidence of stress corrosion cracking in the welded portion or base metal surrounding the welded portion of the c-ring type specimen after the one month period.

Comparative Examples 1-3

Three housings for vehicle occupant protection devices were assembled from containers and endcaps. The containers of the comparative examples were formed by the same process used to form the container of example 1. The endcaps were formed by essentially the same process as the process used to form the endcap of example 1. The only difference between the process used to form the endcap of the comparative examples and the process used to form the endcap of example 1, was the percent that each steel sheet of the comparative examples was reduced during the last pass of each steel sheet through the cold rolling mill.

The steel sheet of comparative example 1 was reduced from a thickness of about 0.099 inches to about 0.079 inches (i.e., about 20%) during the last pass through the cold rolling mill. The steel sheet of comparative example 2 was reduced from a thickness of about 0.095 inches to about 0.078 inches (i.e., about

17.8%) during the last pass through the cold rolling mill. The steel sheet of comparative example 3 was reduced from a thickness of about 0.091 inches to about 0.079 inches (i.e., about 13.1%) during the last pass through the cold rolling mill.

Each of the endcaps so formed was then laser welded to a container to form a housing.

A c-ring type specimen was removed from a welded portion of each of the housings of the comparative examples and placed in 3% NaCl saturated air atmosphere. The c-ring type specimens were maintained at a temperature of about 25°C and subjected to a voltage of about 1.5V from a Ag/AgCl hydrogen cathode charging mechanism. Stress equivalent to 100% of the actual yield strength was applied to the c-ring type specimens for one month.

Analysis by thermal absorption spectrometry and scanning electron microscopy revealed hydrogen embrittlement in the welded portion or base metal surrounding the welded portion of the c-ring type specimens after the one month period.

Moreover, a c-ring type specimen was removed from each of the welded portions of the housing and placed in a 3% NaCl saturated air atmosphere at a temperature

of about 80°C. Stress equivalent to about 100% of the actual yield strength was applied to the c-ring type specimens for one month.

Analysis by thermal absorption spectrometry and scanning electron microscopy showed evidence of stress corrosion cracking in the welded portion or base metal surrounding the welded portion of the c-ring type specimens after the one month period.

Advantages of the present invention should now be apparent. Primarily, the present invention takes advantage of the improved mechanical properties of a housing 18 manufactured from austenitic 301 or austenitic 301N steel of which the composition has been controlled and which has been mechanically treated by controlled hot rolling and cold rolling of the steel. The housing 18 exhibits no evidence of stress corrosion cracking along the weld between the housing components. Furthermore, there is no evidence of stress corrosion cracking of the portion of the housing components adjacent to the weld. Moreover, austenitic 301 steel and austenitic 301N steel with the composition of the present invention and mechanically treated by the method of the present invention exhibits no hydrogen

embrittlement in the weld or portions of the housing components adjacent to the weld.

From the above description of the invention, those skilled in the art will perceive improvements, changes and modifications. Such improvements, changes and modifications within the skill of the art are intended to be covered by the appended claims.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218